

LAMINAR AIR FLOW



LAMINAR AIR FLOW

Laminar Air Flow L-60 Series

Features:

- High visibility due to acrylic plate cover.
- UV lamp.
- Fluorescent lamp.
- Display of usage time.
- Low noise blower.



L60A - L60D

Specifications & Ordering Information :

Item	L60A	L60B	L60C	L60D
External size (WxDxH) mm	1200 x 650 x 1170	900 x 650 x 1170	1200 x 650 x 2040	900 x 650 x 2040
Internal size (WxDxH) mm	1180 x 630 x 768	880 x 630 x 768	1180 x 630 x 768	880 x 630 x 768
Purification rank	ISO Class III			
Rating air flow	11 CFM			
Filtration efficiency	HEPA Filter (99.99% at 0.3 µl)			
Intensity of illumination (Lux)	1014 ~ 1480			
Power (W)	470	430	470	430
Noise dB	≤ 64			
Power supply	115 V 60 Hz / 110 V 50 Hz			
Fluorescent lamp's spec & quantity	36 W x 2EA (FPLM 36 EX - D)	36 W x 1EA (FPLM 36 EX - D)	36 W x 2EA (FPLM 36 EX - D)	36 W x 1EA (FPLM 36 EX - D)
Material	Head: Steel with powder coating Glove Box: 8 T (Thickness) Acrylic			
Catalog No.	48280101	48280102	48280103	48280104